



## VM-4HxI

### 1:4 HDMI Distribution Amplifier

---



The VM-4HxI is a distribution amplifier for HDMI signals with resolutions up to and including WUXGA and 1080p. The unit reclocks and equalizes the signal and distributes it to four identical outputs.

### FEATURES

---

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- Max. Resolution - Up to WUXGA & 1080p.
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support - Deep Color, x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD, CEC.
- 3D Pass-Through.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances.
- Active Output LED.
- Worldwide Power Supply - 100-240V AC.
- Standard 19" Rack Mount Size - 1U. Rack "ears" included.



## VM-4Hxl

### TECHNICAL SPECIFICATIONS

INPUT:	1 HDMI connector.
OUTPUTS:	4 HDMI connectors.
BANDWIDTH:	6.75Gbps (2.25Gbps per graphic channel).
MAX. RESOLUTION:	Up to WUXGA (1920x1200), 1080p.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
CONTROLS:	SELECT and READ buttons for selecting and storing EDID information.
INDICATOR LEDs:	OUTPUTS 1 to 4, and ACTIVE LED.
POWER CONSUMPTION:	100–264V AC, 50/60Hz, 16VA.
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	2.5kg (5.5lbs) approx.
INCLUDED ACCESSORIES:	Power cord, rack "ears".

